






# 智能功率模块接口光耦 Intelligent Power Module Optocoupler

## ATM480

Product Data Sheet

AOTE DCC  
RELEASE



## Pin Configuration

- 1.Anode
- 2.NC
- 3.Cathode
- 4.GND
- 5.VO
- 6.VCC

## 封装逻辑原理图 Encapsulation logic schematic

ATM480 光耦采用高效光电转换技术,结合先进封装工艺,提供输入输出间的可靠隔离,支持SOP6-P、SOP6-W封装形式,适配多样化场景需求。

The ATM480 optocoupler adopts high-efficiency photoelectric conversion technology and advanced packaging processes, providing reliable input-output isolation. It supports package types SOP6-P、SOP6-W to meet diverse application requirements.

## 主要特征 Main features

- 输入-输出隔离电压 $V_{ios}=3750V_{rms}$   
Input output isolation voltage:  $V_{ios}=3750V_{rms}$
- 20 kV/ $\mu s$ 最小共模抑制;20 kV/ $\mu s$  minimum Common Mode Rejection
- 4.5V 至 20V 宽工作电压范围; 4.5V ~ 20V Wide operating VCC Range
- 爬电距离>7.0mm ; Creepage distance > 7.0mm;
- 输入-输出绝缘距离 >0.4mm ; Input-Output insulation Thickness > 0.4mm
- 防潮等级 class1; MSL class1
- 产品符合 ROHS、REACH 及 HF 等环保法规要求;  
The products comply with ROHS, REACH and HF;

## 应用领域 Applications

- 交流/直流无刷电机驱动器 AC/DC brushless motor driver; 高压反馈干扰, 确保电机调速精度与可靠性; High voltage feedback interference ensures the accuracy and reliability of motor speed regulation;
- 工业变频与逆变器Industrial frequency conversion and inverter; 缩短开关死区时间, 优化IGBT/MOSFET的开关效率; Shorten the dead time of the switch, Optimizing the switching efficiency of IGBT/MOSFET
- 工业逆变器与USP电源Industrial inverters and USP power supplies通过高共模瞬态抗扰度 (CMR15kV/ $\mu s$  抵御电压浪涌Resist voltage surges through high common mode transient immunity (CMR>15kV/ $\mu s$ )
- 充电桩与车载充电器Charging stations and car chargers; 隔离车辆与充电设备的通信接口, 防止地电位差导致信号失真; Communication interface between isolated vehicles and charging equipment, Prevent signal distortion caused by ground potential difference;



**◆ 极限参数 Absolute Maximum Ratings (Ta =25°C)**

| 参数<br>Parameter                |                                                 | 符号<br>Symbol | 额定值<br>Rating | 单位<br>Unit |
|--------------------------------|-------------------------------------------------|--------------|---------------|------------|
| 发射端<br>Input                   | 平均输入电流<br>Average Input Current                 | IF(AVG)      | 10            | mA         |
|                                | 峰值瞬态输入电<br>流<br>Peak Transient<br>Input Current | IF(TRAN)     | 1.0           | A          |
|                                |                                                 |              | 40            | mA         |
|                                | 反向电压<br>Reverse Input Voltage                   | VR           | 5             | V          |
|                                | 输入功耗<br>Input Power Dissipation                 | PI           | 45            | mW         |
| 接收端<br>output                  | 平均输出电流<br>Average Output Current                | IO           | 25            | mA         |
|                                | 电源电压<br>Supply Voltage                          | VCC          | 25            | V          |
|                                | 输出电压<br>Output Voltage                          | VO           | -0.5 ~VCC     | V          |
| 总功耗<br>Total Power Dissipation |                                                 | Ptot         | 210           | mW         |
| 隔离电压<br>Isolation voltage      |                                                 | VISO         | 3750          | Vrms       |
| 工作温度<br>Operating Temperature  |                                                 | Topr         | -40 ~+100     | °C         |
| 存储温度<br>Storage Temperature    |                                                 | Tstg         | -55 ~+125     | °C         |

**◆ 推荐操作条件 Recommended Operating Conditions**

| 参数<br>Parameter                     | 符号<br>Symbol | 最小值<br>Min | 最大值<br>Max. | 单位<br>Unit |
|-------------------------------------|--------------|------------|-------------|------------|
| 电源电压<br>Power Supply Voltage        | VCC          | 4.5        | 20          | V          |
| 开启电流<br>Forward Input Current (ON)  | IF(ON)       | 6.0        | 10.0        | mA         |
| 关断电压<br>Forward Input Voltage (OFF) | VF(OFF)      | 0          | 0.8         | V          |
| 操作温度<br>Operating Temperature       | TA           | -40        | +100        | °C         |

**◆ 产品特性参数Product characteristic parameters (Ta =25°C)**

| 参数<br>Parameter |                                                               | 符号<br>Symbol          | 条件<br>Condition               | 最小<br>Min. | 典型<br>Typ. | 最大<br>Max. | 单位<br>Unit |
|-----------------|---------------------------------------------------------------|-----------------------|-------------------------------|------------|------------|------------|------------|
| 发射端<br>Input    | 正向电压<br>Forward Voltage                                       | VF                    | IF =6mA                       | -          | 1.35       | 1.7        | V          |
|                 | 反向击穿电压<br>Reverse Voltage                                     | BVR                   | IR =10uA                      | 5          | -          | -          | V          |
|                 | 开启电流<br>Open the current                                      | IFLH                  | -                             | -          | 3.0        | 5          | mA         |
|                 | 输入正向电压的温度系数<br>Temperature Coefcient of Input Forward Voltage | $\Delta VF/\Delta TA$ | IF =6mA                       | -          | -1.7       | -          | mV/°C      |
|                 | 输入电容<br>Capacitance                                           | C-in                  | V=0,f=1MHz                    | -          | 60         | -          | pF         |
| 接收端<br>Output   | 输出漏电流<br>Output leakage current<br>(Vo=VCC+0.5V)              | IOHH                  | VCC=5V,IF =10mA               | -          | -          | 200        | uA         |
|                 |                                                               |                       | VCC=20V,IF =10mA              | -          | -          | 500        |            |
|                 | 低电平输出短路电流<br>Low level output Short-circuit power             | IOSL                  | VO=VCC=5.5V,<br>VF =0V        | 25         | -          | -          | mA         |
|                 |                                                               |                       | VO =VCC=20V,<br>VF =0V        | 50         | -          | -          |            |
|                 | 高电平输出短路电流<br>High level output Short-circuit power            | IOSH                  | VCC=5.5V<br>IF =6mA,VO =GND   | -          | -          | -25        | mA         |
|                 |                                                               |                       | VCC=20V,<br>IF =6mA,VO =GND   | -          | -          | -50        | mA         |
|                 | 高电平电源电流<br>High Level Supply Current                          | ICCH                  | VCC=5.5V<br>IF =10mA,IO =Open | -          | 1.0        | 2.5        | mA         |
|                 |                                                               |                       | VCC=20V<br>IF =10mA,IO =Open  | -          | 1.2        | 2.5        |            |
|                 | 低电平电源电流<br>Low Level Supply Current                           | ICCL                  | VCC=5.5V<br>VF =0V,IO =Open   | -          | 1.0        | 3          |            |
|                 |                                                               |                       | VCC=20V<br>VF =0V,IO =Open    | -          | 1.2        | 3          |            |
|                 | 低电平输出电压<br>Low Level Output Voltage                           | VOL                   | IOL=6.4mA                     | -          | -          | 0.5        | V          |
|                 | 高电平输出电压<br>High Level Output Voltage                          | VOH                   | IOH=-2.6mA                    | 2.4        | VCC-1.1    | -          | V          |

**◆ 开关特性参数 Switching Specification parameters (Ta =25°C)**

| 参数<br>Parameter                                                            | 符号<br>Symbol | 条件<br>Condition                                             | 最小<br>Min. | 典型<br>Typ.       | 最大<br>Max. | 单位<br>Unit |
|----------------------------------------------------------------------------|--------------|-------------------------------------------------------------|------------|------------------|------------|------------|
| 逻辑低电平传输延迟 Propagation Delay<br>Time to Low Output Level                    | TPHL         | TR/TF =5ns<br>100%duty cycle<br>ZO =50Ω,<br>VO =5V<br>带峰值电容 | -          | 150              | 350        | ns         |
| 逻辑高电平传输延迟 Propagation Delay<br>Time to High Output Level                   | TPLH         |                                                             | -          | 150              | 350        | ns         |
| 脉宽失真 Pulse Width Distortion<br> tPHL-tPLH                                  | PWD          |                                                             | -          | -                | 250        | ns         |
| 传输延迟差 Propagation Delay<br>Diference Between Any Two Parts<br>(tPHL-tPLH)* | PDD          |                                                             | -100       | -                | 250        | ns         |
| 输出上升时间<br>Output Rise Time (10% ~90%)                                      | Tr           |                                                             | -          | 10               | -          | ns         |
| 输出下降时间<br>Output Fall Time (90% ~10%)                                      | Tf           |                                                             | -          | 10               | -          | ns         |
| 输出高电平共模抑制<br>Output High Level Common Mode<br>Transient Immunity           | CMH          | TA =25°C<br> VCM =1000V<br>IF =6.0mA,<br>VCC=5V             | 20         | -                | -          | kV/μs      |
| 输出低电平共模抑制<br>Output Low Level Common Mode<br>Transient Immunity            | CML          | TA =25°C,<br> VCM =1000V<br>VF =0V,VCC=5V                   | 20         | -                | -          | kV/μs      |
| 隔离电阻<br>Input-Output Resistance                                            | RISO         | VI-O ≤ 500V                                                 | -          | 10 <sup>12</sup> | -          | Ω          |
| 隔离电容<br>Input-Output Capacitance                                           | CISO         | VI-O =0V<br>Freq=1.0MHz                                     | -          | 0.6              | -          | pF         |

◆ 电性特性曲线 Electrical characteristic curve ( $T_A = 25^\circ\text{C}$ )

Fig.1 Low level voltage vs. Ambient temperature




Fig.2 High level output current  $I_{OH}$  vs. Ambient temperature




Fig.3 Output voltage vs. Input current




Fig.4 Input current vs. Forward Voltage




Fig.5 Propagation delay vs. Ambient temperature




Fig.6 Output voltage vs. Supply Voltage




Fig.7 Propagation delay vs. Supply voltage




Fig.8 High level output voltage vs. High output current






Fig.9 Low level output voltage vs. Low output current




◆ 延迟时间测试电路 Propagation Delay Time Test Circuit



探针和夹具电容包含在 $C_1$ 和 $C_2$ 中。



|             |      |       |
|-------------|------|-------|
| $R_1$       | 580Ω | 330Ω  |
| $I_{F(ON)}$ | 6 mA | 10 mA |

二极管为1N916或1N3064。






◆ **CMR 测试电路 Test Circuit for Common Mode Transient Immunity**




◆ 外形尺寸Overall dimension

SOP5



推荐焊盘:

Recommended



单位: mm

### ◆ 产品型号命名规则 Order code

AT M480 - UN Y-W(V)(ZZ)

①                      ②                      ③                      ④                      ⑤                      ⑥                      ⑦

- ① 公司代码 Company Code (AT: 奥特 Aote)
- ② 产品系列 Product Series (M480)
- ③ 框架类型 Lead Frame (Cu: 铜框架 Copper)
- ④ 树脂类型 Epoxy Type (H: 无卤 Halogen-free)
- ⑤ 封装形式 Package (S: SOP)
- ⑥ 器件工作温度范围 Device Operating Temperature Range (特殊范围需填或者空白 Special Range need to be filled in or left blank)
- ⑦ 内部补充代码 Internal Supplementary Code (数字或者空白 Number or Non)

### ◆ 印字信息 Marking Information

- 印字中 “” 为奥特品牌LOGO  
“” denotes LOGO
- 印字中 “Y” 代表年份; A(2018),B(2019),C(2020) ... ..  
“Y” denotes YEAR: A(2018), B(2019), C(2020) ... ..
- 印字中 “WW” 代表周号  
“WW” denotes Week' s number
- 印字中 “E” 代表内部代码  
“E” denotes Internal code
- 印字中的 “H” 代表无卤  
“H” denotes Halogen-free





◆ 包装packing

| 封装           | 包装方式                      | 盘数量               | 盒数量              | 箱数量                 | 静电袋规格                        | 盒规格               | 箱(双瓦楞)规格             | 备注                    |
|--------------|---------------------------|-------------------|------------------|---------------------|------------------------------|-------------------|----------------------|-----------------------|
| SOP5         | 编带<br>( $\phi 330$ mm 蓝)  | 3k /盘             | 2 盘/盒            | 10 盒/箱              | 450*390*0.1mm                | 340*60*340mm      | 620*360*365mm        | 保护带 200mm<br>(min)    |
| Package Type | Packing Form              | Quantity per Reel | Quantity per Box | Quantity per Carton | Antistatic Bag Specification | Box Specification | Carton Specification | Note                  |
| SOP5         | Reel( $\phi 330$ mm Blue) | 3k pcs/reel       | 2 reels /box     | 10 boxes /ctn       | 450*390*0.1mm                | 340*60*340mm      | 620*360*365mm        | Guard band 200mm min. |

• 编带包装 Tape & Reel

- 1) 每卷数量: 3000 只。  
Qty/reel: 3000 pcs.
- 2) 每箱数量: 60000 只。  
Qty/ctn: 60000 pcs.
- 3) 内包装: 每盒 2 盘。  
Inner packing: 2reels/box
- 4) 示意图 Schematic:




单位: mm


**◆ 可靠性测试 Reliability Test Items And Conditions**

| 实验项目<br>Test Items                                          | 参考标准<br>Reference | 实验条件<br>Test Conditions               | 时间<br>Time             | 样品数<br>Quantity | 判据<br>Criterion |
|-------------------------------------------------------------|-------------------|---------------------------------------|------------------------|-----------------|-----------------|
| 可焊性<br>Solderability                                        | JESD22-B102       | Tsol= (245±5) °C,<br>t=5s;            | 1 次1 times             | 22              | 0/22            |
| 耐焊接热<br>Resistance to<br>Soldering Heat                     | JESD22-A106       | Tsol= (260±5) °C,<br>t=10s            | 3 次3 times             | 22              | 0/22            |
| 静电放电<br>ESD-HBM                                             | JESD22-A114       | Ta=25°C, HBM<br>(2000V)               | 正反各 3 次<br>P&N 3 times | 10              | 0/10            |
| 高温贮存<br>High emperature<br>Storage                          | JESD22-A103       | Ta=125°C                              | 1000h                  | 22              | 0/22            |
| 低温贮存<br>Low Temperature<br>Storage                          | JESD22-A119       | Ta= -55°C                             | 1000h                  | 22              | 0/22            |
| 冷热冲击<br>Thermal Shock                                       | JESD22-A104       | -55°C(15min)↔<br>125°C(15min)         | 循环 300 次<br>300 cycles | 22              | 0/22            |
| 常温寿命试验<br>Lifespan Test                                     | JESD22-A108       | Ta=25°C, IF=50mA ,<br>Vcc=5V          | 1000h                  | 22              | 0/22            |
| 高温寿命试验<br>DC Operating Life                                 | JESD22-A108       | Ta=110°C, IF=20mA ,<br>Vcc=5V         | 1000h                  | 76              | 0/76            |
| 高温高湿偏压<br>High Temperature<br>High Humidity<br>bias Voltage | JESD22-A101       | Ta =85°C , RH=85%<br>IF=0mA , VCE=64V | 1000h                  | 22              | 0/22            |
| 高温偏压<br>High Temperature<br>bias Voltage                    | JESD22-A108       | Ta =110°C , IF=0mA ,<br>VCE=80V       | 1000h                  | 22              | 0/22            |
| 高压蒸汽试验<br>High pressure steam<br>test                       | JESD22-A102       | P=15PSIG , 121°C,<br>100%RH           | 96h                    | 22              | 0/22            |

### ◆ 回流焊温度曲线图 Solder Reflow Profile




有铅制程 Lead Process



无铅制程 Lead Process

### ◆ 波峰焊温度曲线图 Wave Soldering Profile



### ◆ 手工烙铁焊接 Soldering with hand soldering iron

A. 手工烙铁焊仅用于产品返修或样品测试;

Hand soldering iron is only used for product rework or sample testing;

B. 手工烙铁焊要求: 温度 350°C ± 5°C, 时间 ≤ 3s.

Hand soldering iron requirements: Temperature: 350°C ± 5°C, within 3s.

#### ◆ 注意 Attention

- 奥特半导体实施动态技术迭代机制，产品规格可能随工艺升级调整，最新技术参数以官网发布版本为准。

AOTE implements dynamic technical updates. Specifications are subject to change. Refer to the official website for the latest version.

- 用户需严格遵循本规格书限定的操作条件，因超范围使用（包括但不限于过载、高温、非兼容电路设计）导致的器件失效，不在质量保证范围内。

Users must strictly adhere to specified conditions. Failures caused by misuse (overload, high temperature, incompatible circuits) are excluded from warranty.

- 医疗设备、工业控制等关键场景应用前，需联系技术支持获取定制化验证方案。

Contact technical support for customized validation in critical applications (medical devices, industrial control).

- 本文档有效期至2025年12月31日，后续更新将通过官网公告推送。

This document is valid until Dec 31, 2025. Updates will be notified on the official website.

- 如需对技术参数或应用方案进行进一步确认，欢迎通过以下渠道获取官方支持：

For further clarification on technical specifications or application solutions, please contact us through official channels: