

产品手册

PRODUCT MANUAL

光电耦合器

PHOTOCOUPLER



关注奥特公众号
Follow AOTE Wechat

台湾奥特半导体科技有限公司
Taiwan Aote Semiconductor Technology Co.,Ltd
广东奥特半导体有限公司
Guangdong Aote Semiconductor Co.,Ltd

地址及联系方式
Address and contact information

研发中心：台湾台中市丰原中阳里圆环东路569号
R&D Center: No.569, Huanyuan East Road, Zhongyangli, Fengyuan, Taichung City, Taiwan Province.
销售办事处：广东省深圳市宝安区航城街道黄田社区创建路恒昌荣高新产业园5栋4层
Sales Office: Floor 3, Building 1, No.596 Zhoushi Road, Jiuwei Community, Hangcheng Street, Baoan District, Shenzhen.

 www.aotesemi.com
 sales@aotesemi.com



www.aotesemi.com

COMPANY PROFILE

公司简介

5+

行业经验

20+

认证证书

1000+

现货型号

3000+

服务客户



服务



创新



诚信



高效



奥特半导体科技有限公司 Aote Semiconductor Technology Co., Ltd.

台湾奥特半导体科技有限公司(简称AOTE奥特)成立于2018年,实行“台湾研发、大陆销售”的双核心布局:总部及研发实验室坐落于台湾省台中市,旗下销售公司——广东奥特半导体有限公司设立于深圳。

公司专注于半导体器件的研发、设计、制造与销售,产品涵盖光电耦合器、功率器件芯片、电源管理IC、逻辑器件等,广泛应用于工业控制、新能源汽车、充电桩、智能家居及消费电子电源等领域。

公司已通过ISO9001、ISO14001认证,产品符合RoHS、REACH、SGS环保标准,并取得中国CQC、德国VDE、美国UL等国际安规认证。

AOTE提供从产品选型到方案落地全程专业支持,以技术与质量双轮驱动,为客户交付稳定高效的元器件与系统级方案,共赢产业链未来。

Taiwan AOTE Semiconductor Technology Co., Ltd. (AOTE) was established in 2018, implementing a dual core layout of "research and development in Taiwan and sales in mainland China": the headquarters and research and development laboratory are located in Taichung City, Taiwan Province, and its sales company, Guangdong AOTE Semiconductor Co., Ltd., is located in Shenzhen.

The company focuses on the research and development, design, manufacturing, and sales of semiconductor devices, with products including optocouplers, power device chips, power management ICs, logic devices, etc., widely used in industrial control, new energy vehicles, charging stations, smart homes, and consumer electronics power supplies.

The company has passed ISO9001 and ISO14001 certifications, and its products comply with RoHS, REACH, SGS environmental standards. It has also obtained international safety certifications such as China CQC, Germany VDE, and the United States UL.

AOTE provides full professional support from product selection to solution implementation, driven by both technology and quality, to deliver stable and efficient components and system level solutions to customers, achieving a win-win future for the industry chain.

Corporate Culture

企业文化



企业
愿景

成为世界有影响力的领先的光电耦合器
制造商和解决方案供应商

To become a leading optocoupler with global influence Manufacturers and solution providers



企业
使命

让奥特电耦合器更敏捷高效

Make the Otter optocoupler more agile and efficient



企业
精神

诚信、创新、尊重、感恩、合作 高效、分享、共赢、传递价值

Integrity, innovation, respect, gratitude, efficient cooperation, sharing, win-win, and value transmission



正品保证 

质量保证 

无忧退换 

可开发票 

长期现货 

原厂供应 

CORE STRENGTHS

核心优势



供应商管理

奥特拥有完整的供应商评估体系，安全、稳定的供应商队伍。
Aote has a complete supplier evaluation system and a safe and stable supplier team.



制程品质管理

奥特一直秉承着“质量第一”的管理思想，精益求精，做到“不接受，不制造、不流出”不良品。
Aote has always adhered to the management philosophy of "quality first", striving for excellence, and achieving the goal of "not accepting, not manufacturing, and not exporting" defective products.



客诉管理

奥特拥有专业的客服团队，能高效处理客户抱怨和投诉，承诺 48 小时内完成快速反应及处理，72 小时内给出基本原因分析及改善计划，一般问题7个工作日内回复完整的 8D 报告。
Aote has a professional customer service team that can efficiently handle customer complaints and grievances, with a commitment of 48 hoursComplete rapid response and handling within 72 hours, provide basic cause analysis and improvement planProvide a complete 8D report within 7 working days for general questions.



有害物质管理

奥特具备 RoHS1.0、RoHS2.0 检测能力，成品按封装形式1次/年进行第三方检测并提供检测报告。
Autotech has the ability to detect RoHS1.0 and RoHS2.0, and the finished products are packaged once a yearThird party testing and providing testing reports.



体系管理

实验室具备独立进行 RA 测试和 FA 分析能力，测试项目包含HAST、PCT、HTOL、HTRB、WHTOL、HT/HH、H3TRB、TC、Salt Test 等
The laboratory has the ability to independently conduct RA testing and FA analysis, and the testing projects includeHAST, PCT, HTOL, HTRB, WHTOL, HT/HH, H3TRB, TC, Salt Test, etc

PRODUCT ADVANTAGES

产品优势



高效低耗 | 驱动能力优异
Efficient and low consumption, excellent driving capability



高稳隔离 | 适配复杂工况
High stability isolation, suitable for complex working conditions



兼容替代 | 降本增效显著
Compatible substitution, significantly reducing costs and increasing efficiency



小巧节能 | 贴合产业趋势
Compact and energy-saving, in line with industry trends

依托自主核心技术，奥特半导体全系光耦产品在性能、适配性、稳定性、实用性上实现全方位升级，精准解决行业传统产品损耗高、稳定性差、替换成本高、环境适配性弱等痛点，成为进口替代的优选方案。

Leveraging proprietary core technologies, OptiSemiconductors' full range of optocoupler products has achieved comprehensive upgrades in performance, adaptability, stability, and practicality. These advancements precisely address industry pain points such as high power consumption, poor stability, elevated replacement costs, and weak environmental adaptability in traditional products, making them an optimal solution for import substitution.



CONTENTS

目录

01 应用领域
Application field 01/0202 封装说明
Encapsulation Description 03/04封装形式
产品型号定义03 产品选型表
Product Selection Sheet 05/0604 晶体管光耦
Transistor optocoupler 07/10

晶体管光耦 (AC) Transistor optocoupler (AC)	
DIP-4/DIP4-M/SMD-4	AT814
SOP-4	AT354
SSOP-4	AT3H4
SOP-16	AT3H44

晶体管光耦 (DC) Transistor optocoupler (DC)	
DIP-4/DIP4-M/SMD-4	AT816/AT817/AT851/AT451/AT8016
SOP-4	AT357/AT358/AT818
SSOP-4	AT3H7
LSOP-4	AT101X
DIP-6/SMD-6	AT4NXX
DIP-8/SMD-8	AT826/ATN826/AT827/ATN827

05 达林顿光耦
Darlington optocoupler 11/12

DIP-4/DIP4-M	AT852/AT815
SSOP-4	AT215
SOP-4	AT452/AT415
DIP-6/SMD-6	AT4N29/AT4N30/AT4N31/AT4N32/AT4N33
DIP-8/SMD-8	AT6N138/AT6N139/AT825

06 可控硅光耦
Thyristor optocoupler 13/18

可控硅光耦 (NZC) Thyristor optocoupler (NZC)	
SOP-4	ATM301X/ATM302X/ATM305X/ATM307X
DIP-4/SMD-4	AT52X/AT55X
DIP-6/SMD-6	AT301X/AT302X/AT305X/AT307X
DIP-5/SMD-5	AT2011/AT2021/AT2051/AT2071
DIP-5/SMD-5	AT2022/AT2032/AT2052/AT2072
DIP-5/SMD-5	AT2013/AT2023/AT2053/AT2073
DIP-7/SMD-7	AT0223/AT1223/AT2223/AT3223

可控硅光耦 (ZC) Thyristor optocoupler (ZC)	
SOP-4	ATM303X/ATM304X/ATM306X/ATM308X
DIP-6/SMD-6	AT303X/AT304X/AT306X/AT308X
DIP-5/SMD-5	AT2031/AT2041/AT2061/AT2081
DIP-5/SMD-5	AT2032/AT2042/AT2062/AT2082
DIP-5/SMD-5	AT2033/AT2043/AT2063/AT2083
SOP-4	AT53X/AT54X/AT56X/AT58X
DIP-7/SMD-7	AT0213/AT1213/AT2213/AT3213

07 光继电器光耦
Optical relay optocoupler 19/20

SOP-4	AT172/AT173/AT174/AT175/AT176/AT1722
DIP-4/SMD-4/DIP4-M	AT212/AT213/AT214/AT216
DIP-8/SMD-8	AT222/AT223/AT224/AT226/AT227
WSOP-16	ATS258
DIP-6/SMD-6	AT252/ATV252/ATV253/ATV254
SMD-5	ATY251/ATY258A

08 高速光耦
High speed optocoupler 21/24

DIP-6/SMD-6	ATH11LX
DIP-8/SMD-8/SOP-8	ATN772X/ATC072X
SOP-5	ATM720/ATM721/ATM723
SOP-5	ATM5XX/ATM6XX/ATW6XX
SOP6-P/SOP-W	ATW501/ATW511/ATW720/ATW721/ATW723
WDIP-8/WSMD-8/WSOP-8	ATN261L/ATC261L
DIP-8/SMD-8	AT6N13X/ATN13X
SOP-8	AT063X/AT053X
SOP-8	ATC74L/AT074L/AT075L/ATC64L
SOP-8/WSOP-8	AT05XX/ATC5XX/AT06XX/ATC6XX
WDIP-10/WSMD-10	AT2601
WSOP-16	AT6N437

09 栅极驱动光耦
Gate driven optocoupler 25/28


DIP-8/SMD-8/DIP8-M	AT3150/AT3120/ATN3150/ATN3150
DIP-8/SMD-8/DIP8-M	AT350/ATN350/AT03XX
SOP-5	ATM34X/AT155
SOP6-P/SOP6-W	AT314/AT34X
WSOP-16	AT330J/AT331J/AT332J/AT333J/AT316

10 智能功率模块化接口光耦
Intelligent power modular interface optocoupler 29/30

SOP6-P/SOP6-W	AT480/AT481
SOP-5	ATM480/ATM481/ATM456
DIP-8/SMD-8	AT4504/ATC4504/ATN4504
DIP-8/SMD-8	AT4506/ATC4506/ATN4506

11 光隔离运算放大器
Optical isolation operational amplifier 31/32

DIP-8/SOP-8	AT7840/ATC790/ATC79A/ATC79B/ATH790
WSOP-8	ATC87AT/ATC87BT

12 品牌型号对应参照表
Brand and Model Corresponding Reference Table 33/40

APPLICATION FIELD

应用领域

► 01


工业控制是机器设备或生产过程在不需人工直接干预的情况下按预期的目标实现测量、操纵等信息处理和过程控制的统称。在工业控制系统中，存在着各种各样的干扰，使用光隔离器可以实现隔离、抗干扰的效果。奥特的栅极驱动光耦(AT3120、AT341)能够对设备前端发出的驱动信号进行隔离保护，其和晶体管光耦(AT817、AT357等)实现了低压数字电路和高压驱动电路之间的电气隔离，从而避免工控设备初次级悬殊的压差带来的安全隐患。



工业控制 Industrial Control

► 02

社会大众健康生活的检测、预防，治疗过程中和医疗设备、仪器是离不开的。奥特光耦抗干扰能力强、体积小，输入输出两端完全绝缘、抑制电噪声和瞬态干扰、消除接地回路等作用使医疗设备实现完全隔离的理想器件。奥特的高速光耦(如 AT6N137、ATW501、ATW601 等)用于电源和电机控制电路、数据通信、数字逻辑接口电路栅极驱动光耦(AT3120、AT341 等)驱动IGBT 和功率 MOSFET器件，实现电机控制和功率转换



医疗设备 Medical equipment

► 03

在全球能源不断缩减、提倡节能减排的大背景下，新能源汽车在市场中占比日益增加，存在全面取代燃油车的趋势，汽车是肩负着人员运输安全使命的交通工具。新能源汽车电池充电、BMS 管理、电控等系统中使用的奥特光继电器(AT117x、AT22x、ATY258、ATS258等)响应速度快，灵敏度高，导通电阻小，漏电流小等特点能够更大地利用电池存储能力和循环寿命；高速光耦(AT6N137、ATO74L、ATO631等)的高速响应为汽车控制系统指挥执行系统提供和采集数据；智能栅极驱动光耦(AT33xJ 系列)更高的输出峰值电流、更强的抗扰能力，具有可编程故障检测、欠压锁定的特点用于驱动电隔离、通信、过程控制等系统。



新能源 New energy

► 04

开关电源是一种高频电能转换装置，是利用电子开关器件通过控制电路快速地“开通”和“关断”，对输入电压进行脉宽调制，从而实现 AC-DC、DC-DC、DC-AC 电压变换。奥特晶体管光耦(AT817/AT1018/AT1019等)在开关电源中将进线220V高压和输出低压两端隔离，同时提供反馈信号至前端控制电路和保护电路，控制驱动电路输出相应的 PWM 信号，以控制开关功率管的工作状态，从而保证后端设备及使用人员的安全和保护输出电压的稳定。



电源 Power supply

► 05

光伏发电是一种利用太阳能电池半导体材料的光伏效应，将太阳辐射能直接转换为电能的一种新型发电系统，搭配储能系统可以对能源利用达到最大化。奥特光继电器(ATY258/ATS258/1500V)在光伏储能产品上做为信号检测、绝缘检测应用，具有输出端子关断耐压高、初次侧高绝缘耐压特性(5000V以上绝缘耐压)，给高压储能设备提供安全保障；ATN201高精度线性光耦，提供更高精度的信号采样数据。



光伏逆变 Photovoltaic Inverter


► 06

家用电器使人们从繁重、琐碎、费时的家务劳动中解放出来，提供了丰富多彩的文化娱乐条件，是现代家庭生活的必需品。日用家电的高功率、高电压会有一定的安全隐患，这就需要用到隔离器件来消除电平转换时悬殊的压差带来的不安全因素。奥特晶体管光耦(AT817、AT1018、AT1019等)电压采样和信号反馈；高速光耦(ATM60x、ATW60x、AT6N137、AT0601等)用于检测与保护线路；可控硅光耦(ATX223、ATX213、AT305x、AT306x等)能在高压、强电流的条件下工作，且工作过程可以控制，用于可控整流交流调压、无触点电子开关、逆变及变频等电子电路中。



家用电器 Home appliances

PACKAGE FORM
封装形式




Package	size A*B*C
DIP-4/SMD-4/DIP4-M	6.5*4.6*3.5
DIP-6/SMD-6/DIP6-M	7.2*6.5*3.5
DIP-7/SMD-7/DIP7-M	9.7*6.5*3.5
DIP-8/SMD-8/DIP8-M	9.7*6.5*3.5
SOP-4	4.6*4.2*2.0
SOP-5	4.6*4.2*2.0
SOP-8	5.2*4.2*3.2

Package	size A*B*C
SOP-16	10.3*4.6*2.1
SSOP-4	4.6*2.7*2.1
LSOP-4	7.6*3.6*2.0
SOP6-W/SOP6-P	6.8*4.6*3.2
WDIP-8	10.7*7.5*3.5
WDIP-10	13.2*7.5*3.5
WSOP-8	6.5*5.2*3.2



PRODUCT MODEL DEFINITION
产品型号定义

AT 817 X - UN Y - W



备注:
CTR档位(代码:A、B、C、D)
框架类型:(Cu:铜框架, Fe:铁框架)
封装形式:(D:DIP, S:SMD; M:DIP-M)

PRODUCT SELECTION TABLE

产品选型表

奥特产品选型表

晶体管光耦	AT816 AT817	AT851 AT814	AT357 AT354	AT8801 AT101X	AT826 AT827	AT451	AT3H7 AT8016	AT2514 ATN201	ATN200 ATN201	ATN826 ATN827
达林顿光耦	AT815 AT852	AT825 AT415	AT452 AT215	AT4NXX ATN825	AT6N138 AT6N139	ATN6N138 ATN6N139	ATN825			
光继电器	AT21X AT41X	AT22X AT17X	ATY258 ATS258	ATY258H ATS258H	AT176 AT42X	AT1722 AT2122	ATV21X ATV25X	AT2222 AT41XS	ATY259 ATS259	ATV41X ATV45X
可控硅光耦	AT52X AT55X	AT56X AT58X	AT302X AT305X	AT306X AT308X	ATM302X ATM305X	ATM306X ATM308X	ATX213 ATX223	AT202X AT205X	AT206X AT208X	
高速光耦	6N135 6N136	6N137 AT7720	ATM511 ATM611	ATW511 ATW611	ATM721 ATW720	ATN6N135 ATN6N136	H11L1 ATC64L	ATN6N137 ATN261L	ATC53X ATC63X	ATM723 ATW723
栅极驱动光耦	AT3120 AT3150	ATM341 ATM314	AT350 AT341	AT314 AT343	ATM343 ATN3140	AT0341 AT0314	AT3140 AT0343	ATN3120 ATN3150		
智能栅极驱动光耦	AT330J	AT332J	AT316J	AT331J	AT333J	AT337J	AT339J			
智能功率模块接口光耦	AT4504	AT4506	AT480	ATM480	ATM481	AT481	ATN4504	ATN4506	ATC4504	ATC4506
光隔离运算放大器	AT7840	ATC87AT	ATC87BT	ATH87AT	ATH87BT	ATC790	ATH790			

晶体管光耦

TRANSISTOR OPTOCOUPLER

晶体管光耦是由发光二极管和光电晶体管组成的光电耦合器,通过光电效应和晶体管放大特性,实现电信号的光学隔离与传输确保信号稳定可靠。晶体管光耦包含晶体管光耦(交流)和晶体管光耦(直流)两大类。

Transistor optocoupler is a optocoupler composed of light-emitting diodes and phototransistors. Through the photoelectric effect and transistor amplification characteristics, it achieves optical isolation and transmission of electrical signals to ensure signal stability and reliability. Transistor optocouplers include two categories: transistor optocouplers (AC) and transistor optocouplers (DC)

产品特性

Product Features

- 具有大电流传输比;
- 高耐压、低输入电流;
- 可用于隔离高压电路和低压电路;
- 安规认证: CQC/UL/VDE/SGS 国网认证等;
- 产品认证: ROHS&REACH/无卤等;
- It has a high current transmission ratio;
- High voltage resistance and low input current;
- Can be used to isolate high-voltage circuits from low-voltage circuits;
- Safety Certification: CQC/UL/VDE/SGS National Grid Certification, etc;
- Product Certifications: ROHS & REACH/Flame Retardant Free, etc;

应用领域

Application field

- 家用电器
- 开关电源
- 智能电表
- Household appliances
- Switching power supply
- Smart electricity meter







封装形式



Package form








技术参数

Technical Specifications







Input Type:AC	Part Number	CTR			VF (V)	BVCEO (V)	Viso (Vrms)
		CTR (档位)	CTR (%)	@IF(mA)/Vce(V)			
DIP-4/SMD-4/DIP4-M » 	AT814	A	50-150	±1/5	1.2-1.4	80	5000
		B	100-300	±1/5	1.2-1.4	80	5000
		--	20-300	±1/5	1.2-1.4	80	5000
SOP-4 » 	AT354	A	50-150	±1/5	1.2-1.4	80	3750
		B	100-300	±1/5	1.2-1.4	80	3750
		--	20-300	±1/5	1.2-1.4	80	3750
SSOP-4 » 	AT3H4	A	50-150	±1/5	1.2-1.4	80	3750
		B	100-300	±1/5	1.2-1.4	80	3750
		--	20-300	±1/5	1.2-1.4	80	3750
SOP-16 » 	AT3H44	A	50-150	±1/5	1.2-1.4	80	3750
		B	100-300	±1/5	1.2-1.4	80	3750
		--	20-300	±1/5	1.2-1.4	80	3750

Input Type:DC	Part Number	CTR			VF (V)	BVCEO (V)	Viso (Vrms)
		CTR (档位)	CTR (%)	@IF(mA)/Vce(V)			
DIP-4/SMD-4/DIP4-M » 	AT816	A	80-160	1/5	1.1-1.4	80	5000
		B	130-260	1/5	1.1-1.4	80	5000
		C	200-400	1/5	1.1-1.4	80	5000
		D	300-600	1/5	1.1-1.4	80	5000
DIP-4/SMD-4/DIP4-M » 	AT817	A	80-160	1/5	1.2-1.4	80	5000
		B	130-260	1/5	1.2-1.4	80	5000
		C	200-400	1/5	1.2-1.4	80	5000
		D	300-600	1/5	1.2-1.4	80	5000
		--	80-600	1/5	1.2-1.4	80	5000
SOP-4 » 	AT357	A	80-160	1/5	1.2-1.4	80	3750
		B	130-260	1/5	1.2-1.4	80	3750
		C	200-400	1/5	1.2-1.4	80	3750
		D	300-600	1/5	1.2-1.4	80	3750
		--	80-600	1/5	1.2-1.4	80	3750

技术参数 Technical Specifications

Input Type:DC	Part Number	CTR			VF (V)	BVCEO (V)	Viso (Vrms)
		CTR(档位)	CTR(%)	@IF(mA)/Vce(V)			
SSOP-4 » 	AT3H7	A	80-160	1/5	1.2-1.4	80	3750
		B	130-260	1/5	1.2-1.4	80	3750
		C	200-400	1/5	1.2-1.4	80	3750
		D	300-600	1/5	1.2-1.4	80	3750
		--	80-600	1/5	1.2-1.4	80	3750
LSOP-4 » 	AT101X	AT1010	50-600	5/5	1.2-1.4	80	5000
		AT1012	63-125	10/5	1.2-1.4	80	5000
		AT1013	100-200	10/5	1.2-1.4	80	5000
		AT1014	160-320	10/5	1.2-1.4	80	5000
		AT1016	100-300	10/5	1.2-1.4	80	5000
		AT1017	80-160	5/5	1.2-1.4	80	5000
		AT1018	130-260	5/5	1.2-1.4	80	5000
DIP-4/SMD-4/DIP4-M » 	AT851	--	50-600	1/5	1.2-1.4	350	5000
	AT451	--	80-600	1/5	1.2-1.4	350	3750
DIP-6/SMD-6 » 	AT4NXX	4N25	20	10/10	1.2-1.5	30	5000
		4N26	20	10/10	1.2-1.5	30	5000
		4N38	20	10/10	1.2-1.5	30	5000
		4N27	10	10/10	1.2-1.5	30	5000
		4N28	10	10/10	1.2-1.5	30	5000
		4N35	100	10/10	1.2-1.5	30	5000
		4N36	100	10/10	1.2-1.5	30	5000
		4N37	100	10/10	1.2-1.5	30	5000
DIP-8/SMD-8 » 	AT826 ATN826	C	200-400	5/5	1.0-1.3	80	5000
		D1	300-450	5/5	1.0-1.3	80	5000
		D2	380-600	5/5	1.0-1.3	80	5000
		--	200-600	5/5	1.0-1.3	80	5000
	AT827 ATN827	--	80-600	1/5	1.2-1.4	80	5000

技术参数 Technical Specifications

Input Type:DC	Part Number	CTR			VF (V)	BVCEO (V)	Viso (Vrms)
		CTR(档位)	CTR(%)	@IF(mA)/Vce(V)			
SOP-4 » 	AT358	--	50-600	1/5	1.2-1.4	80	3750
	AT818	--	50-600	1/5	1.2-1.4	80	3750
DIP-4/DIP4-M » 	AT8016	--	0.1-1.5	5/5	1.2-1.4	30	5000
SOP-4 » 	AT8801	A	80-160	1/5	1.2-1.4	75	3750
		B	130-260	1/5	1.2-1.4	75	3750
		C	200-400	1/5	1.2-1.4	75	3750
		--	80-400	1/5	1.2-1.4	75	3750
SSOP-4 » 	AT8801	A	80-160	1/5	1.2-1.4	75	3750
		B	130-260	1/5	1.2-1.4	75	3750
		C	200-400	1/5	1.2-1.4	75	3750
		--	80-400	1/5	1.2-1.4	75	3750
LSOP-4 » 	AT8801	A	80-160	1/5	1.2-1.4	75	5000
		B	130-260	1/5	1.2-1.4	75	5000
		C	200-400	1/5	1.2-1.4	75	5000
		--	80-400	1/5	1.2-1.4	75	5000
DIP-4/SMD-4/DIP4-M » 	AT8801	A	80-160	1/5	1.2-1.4	75	5000
		B	130-260	1/5	1.2-1.4	75	5000
		C	200-400	1/5	1.2-1.4	75	5000
		--	80-400	1/5	1.2-1.4	75	5000

达林顿光耦

DARLINGTON OPTOCOUPLER

达林顿光耦是一种高性能光电耦合器，结合发光二极管和高增益光检测器，通过达林顿结构增强电流增益，实现高效电气隔离与电流输出。

Darlington optocoupler is a high-performance optocoupler that combines light-emitting diodes and high gain photodetectors to enhance current gain through Darlington structure, achieving efficient electrical isolation and current output.

产品特性

Product Features

- 高增益，增强信号；
- 高隔离度，避免电气噪声的干扰；
- 高速响应，可在微妙级别内完成信号传输与转换；
- 安规认证：CQC/UL/VDE/SGS国网认证等；
- 产品认证：ROHS&REACH/无卤等；
- High gain, enhanced signal;
- High isolation to avoid interference from electrical noise;
- High speed response, capable of completing signal transmission and conversion at a subtle level;
- Safety Certification: CQC/UL/VDE/SGS National Grid Certification, etc;
- Product Certifications: ROHS & REACH/Flame Retardant Free, etc;

应用领域

Application field

- 电力控制系统
- 医疗设备
- 工业设备
- Power control system
- Medical equipment
- Industrial equipment











封装形式

Package form



技术参数 Technical Specifications

Technical Specifications	Part Number	CTR			VF (V)	BVCEO (V)	Viso (Vrms)
		CTR(档位)	CTR(%)	@IF(mA)/Vce(V)			
SOP-4/DIP-4/DIP4-M » 	AT452	—	1000-7500	1/2	1.2-1.4	350	3750
	AT852	—	1000-7500	1/5	1.2-1.4	350	5000
SSOP-4 » 	AT215	—	600-7500	1/2	1.2-1.4	40	3750
SOP-4 » 	AT415	—	600-7500	1/2	1.2-1.4	40	3750
DIP-6/SMD-6 » 	—	AT4N29	100	10/10	1.3-1.5	50	5000
		AT4N30	100	10/10	1.3-1.5	50	5000
		AT4N31	50	10/10	1.3-1.5	50	5000
		AT4N32	500	10/10	1.3-1.5	50	5000
		AT4N33	500	10/10	1.3-1.5	50	5000
DIP-8/SMD-8 » 	—	AT6N138	400-2000	0.5/4.5	1.4	80	5000
		AT6N139	400-2000	0.5/4.5	1.4	80	5000
		ATN138	400-2000	0.5/4.5	1.4	80	5000
		ATN139	400-2000	0.5/4.5	1.4	80	5000
DIP-4/SMD-4 » 	AT815	—	600-7500	1/5	1.2-1.4	40	5000
DIP-8/SMD-8 » 	AT825	—	600-7500	1/5	1.2-1.4	40	5000
	ATN825	—	600-7500	1/5	1.2-1.4	40	5000
SOP-16 » 	AT2154	—	600-7500	1/5	1.2-1.4	40	3750

可控硅光耦

THYRISTOR OPTOCOUPLER

可控硅光耦利用光信号在电路间传输,实现电气隔离与交流电控制,由发光二极管和光电双向晶闸管组成,是交流负载控制的理想选择,可控硅光耦包含随机相位双向可控硅光耦和零交叉双向可控硅光耦两大类。

Controllable silicon optocouplers use optical signals to transmit between circuits, achieving electrical isolation and AC control. They are composed of light-emitting diodes and optoelectronic bidirectional thyristors, making them an ideal choice for AC load control. Controllable silicon optocouplers include two categories: random phase bidirectional controllable silicon optocouplers and zero crossing bidirectional controllable silicon optocouplers.

产品特性

Product Features

- 采用MOSFET作为开关管,提高了开关速度;
- 内部采用MOSFET结构,体积缩小,重量只有普通三端可控硅的1/3;
- 采用独特热保护技术,工作温度范围宽,延长使用寿命;
- 安规认证:CQC/UL/VDE/SGS国网认证等;
- 产品认证:ROHS&REACH/无卤等;
- Using MOSFET as the switching transistor improves the switching speed;
- Internally adopting MOSFET structure, the volume is reduced and the weight is only one-third of that of ordinary three terminal thyristors;
- Adopting unique thermal protection technology, the working temperature range is wide, extending the service life;
- Safety certification: CQC/UL/VDE/SGS State Grid certification, etc;
- Product Certifications: ROHS & REACH/Flame Retardant Free, etc;

应用领域

Application field

- 家用电器
- 高压交流开关
- 灯光控制器
- household appliances
- High voltage AC switch
- Lighting Controller









封装形式

Package form









技术参数




Technical Specifications

Non-zero Crossing Type:NZC	Part Number	IFT(mA)	VF (V)	VDRM(V)	ITSM(A)	PC(mA)	Viso (Vrms)
	ATM3011	15	1.23-1.5	250	1	300	3750
	ATM3021	15	1.23-1.5	400	1	300	3750
	ATM3051	15	1.23-1.5	600	1	300	3750
	ATM3071	15	1.23-1.5	800	1	300	3750
	ATM3012	10	1.23-1.5	250	1	300	3750
	ATM3022	10	1.23-1.5	400	1	300	3750
	ATM3052	10	1.23-1.5	600	1	300	3750
	ATM3072	10	1.23-1.5	800	1	300	3750
	ATM3013	5	1.23-1.5	250	1	300	3750
	ATM3023	5	1.23-1.5	400	1	300	3750
	ATM3053	5	1.23-1.5	600	1	300	3750
	ATM3073	5	1.23-1.5	800	1	300	3750
	ATM3020	30	1.23-1.5	400	1	300	3750
	ATM3021	15	1.23-1.5	400	1	300	3750
	ATM3022	10	1.23-1.5	400	1	300	3750
	ATM3023	5	1.23-1.5	400	1	300	3750
	AT520	20-30	1.18-1.5	400	1	300	5000
	AT521	10-15	1.18-1.5	400	1	300	5000
	AT522	5-10	1.18-1.5	400	1	300	5000
	AT523	3-5	1.18-1.5	400	1	300	5000
	AT551	10-15	1.18-1.5	600	1	300	5000
	AT552	5-10	1.18-1.5	600	1	300	5000
	AT553	3-5	1.18-1.5	600	1	300	5000







技术参数 Technical Specifications

Non-zero Crossing Type:NZC	Part Number	IFT(mA)	VF (V)	VDRM(V)	ITSM(A)	PC(mA)	Viso (Vrms)
DIP-6/SMD-6 » 	AT3011	15	1.23-1.5	250	1	300	5000
	AT3021	15	1.23-1.5	400	1	300	5000
	AT3051	15	1.23-1.5	600	1	300	5000
	AT3071	15	1.23-1.5	800	1	300	5000
	AT3012	10	1.23-1.5	250	1	300	5000
	AT3022	10	1.23-1.5	400	1	300	5000
	AT3052	10	1.23-1.5	600	1	300	5000
DIP-6/SMD-6 » 	AT3072	15	1.23-1.5	800	1	300	5000
	AT3013	5	1.23-1.5	250	1	300	5000
	AT3023	5	1.23-1.5	400	1	300	5000
	AT3053	5	1.23-1.5	600	1	300	5000
	AT3073	5	1.23-1.5	800	1	300	5000
DIP-5/SMD-5 » 	AT2011	15	1.23-1.5	250	1	300	5000
	AT2021	15	1.23-1.5	400	1	300	5000
	AT2051	15	1.23-1.5	600	1	300	5000
	AT2071	15	1.23-1.5	800	1	300	5000
	AT2022	10	1.23-1.5	250	1	300	5000
DIP-5/SMD-5 » 	AT2032	10	1.23-1.5	400	1	300	5000
	AT2052	10	1.23-1.5	600	1	300	5000
	AT2072	10	1.23-1.5	800	1	300	5000
	AT2013	5	1.23-1.5	250	1	300	5000
DIP-5/SMD-5 » 	AT2023	5	1.23-1.5	400	1	300	5000
	AT2053	5	1.23-1.5	600	1	300	5000
	AT2073	5	1.23-1.5	800	1	300	5000
	AT0223	30	1.23-1.5	400	1	300	5000
DIP-7/SMD-7 » 	AT1223	15	1.23-1.5	400	1	300	5000
	AT2223	10	1.23-1.5	400	1	300	5000
	AT3223	5	1.23-1.5	400	1	300	5000





技术参数 Technical Specifications

Zero Crossing Type:ZC	Part Number	IFT(mA)	VF (V)	VDRM(V)	ITSM(A)	PC(mA)	Viso (Vrms)
SOP-4 » 	ATM3031	15	1.23-1.5	250	1	300	3750
	ATM3041	15	1.23-1.5	400	1	300	3750
	ATM3061	15	1.23-1.5	600	1	300	3750
	ATM3081	15	1.23-1.5	800	1	300	3750
SOP-4 » 	ATM3032	10	1.23-1.5	250	1	300	3750
	ATM3042	10	1.23-1.5	400	1	300	3750
	ATM3062	10	1.23-1.5	600	1	300	3750
	ATM3082	10	1.23-1.5	800	1	300	3750
SOP-4 » 	ATM3033	5	1.23-1.5	250	1	300	3750
	ATM3043	5	1.23-1.5	400	1	300	3750
	ATM3063	5	1.23-1.5	600	1	300	3750
	ATM3083	5	1.23-1.5	800	1	300	3750

技术参数 Technical Specifications

Zero Crossing Type:ZC	Part Number	IFT(mA)	VF (V)	VDRM(V)	ITSM(A)	PC(mA)	Viso (Vrms)
DIP-6/SMD-6 » 	AT3031	15	1.23-1.5	250	1	300	5000
	AT3041	15	1.23-1.5	400	1	300	5000
	AT3061	15	1.23-1.5	600	1	300	5000
	AT3081	15	1.23-1.5	800	1	300	5000
DIP-6/SMD-6 » 	AT3032	10	1.23-1.5	250	1	300	5000
	AT3042	10	1.23-1.5	400	1	300	5000
	AT3062	10	1.23-1.5	600	1	300	5000
	AT3082	10	1.23-1.5	800	1	300	5000
DIP-6/SMD-6 » 	AT3033	5	1.23-1.5	250	1	300	5000
	AT3043	5	1.23-1.5	400	1	300	5000
	AT3063	5	1.23-1.5	600	1	300	5000
	AT3083	5	1.23-1.5	800	1	300	5000
DIP-5/SMD-5 » 	AT2031	15	1.23-1.5	250	1	300	5000
	AT2041	15	1.23-1.5	400	1	300	5000
	AT2061	15	1.23-1.5	600	1	300	5000
	AT2081	15	1.23-1.5	800	1	300	5000
DIP-5/SMD-5 » 	AT2032	10	1.23-1.5	250	1	300	5000
	AT2042	10	1.23-1.5	400	1	300	5000
	AT2062	10	1.23-1.5	600	1	300	5000
	AT2082	10	1.23-1.5	800	1	300	5000
DIP-5/SMD-5 » 	AT2033	5	1.23-1.5	250	1	300	5000
	AT2043	5	1.23-1.5	400	1	300	5000
	AT2063	5	1.23-1.5	600	1	300	5000
	AT2083	5	1.23-1.5	800	1	300	5000

技术参数 Technical Specifications

Zero Crossing Type:ZC	Part Number	IFT(mA)	VF (V)	VDRM(V)	ITSM(A)	PC(mA)	Viso (Vrms)
SOP-4 » 	AT531	15	1.23-1.5	250	1	300	3750
	AT541	15	1.23-1.5	400	1	300	3750
	AT561	15	1.23-1.5	600	1	300	3750
	AT581	15	1.23-1.5	800	1	300	3750
SOP-4 » 	AT532	10	1.23-1.5	250	1	300	3750
	AT542	10	1.23-1.5	400	1	300	3750
	AT562	10	1.23-1.5	600	1	300	3750
	AT582	10	1.23-1.5	800	1	300	3750
SOP-4 » 	AT533	5	1.23-1.5	250	1	300	3750
	AT543	5	1.23-1.5	400	1	300	3750
	AT563	5	1.23-1.5	600	1	300	3750
	AT583	5	1.23-1.5	800	1	300	3750
DIP-7/SMD-7 » 	AT0213	10	1.3	600	3	800	5000
	AT1213	10	1.3	600	6	800	5000
	AT2213	10	1.3	600	9	800	5000
	AT3213	10	1.3	600	12	800	5000

光继电器光耦

OPTICAL RELAY OPTOCOUPLER

固态继电器光耦是一种特殊的光电耦合器,通过光信号控制通断,由发光二极管、光电探测器与MOSFET组成,高效可靠,适用于现代电子系统。

A solid-state relay optocoupler is a specialized photoelectric coupler that controls switching via optical signals, consisting of an LED, photodetector, and MOSFET. It is efficient, reliable, and suitable for modern electronic systems.

产品特性

Product Features

- 具有良好的隔离性,输入端和输出端完全实现电隔离;
- 发光与光敏器件光谱匹配理想,响应迅速,传输效率高易于连接逻辑电路;
- 单方向传输光信号,有效地阻断电路的电气连接,但不会切断他们之间的信号传输;
- 安规认证: CQC/UL/VDE/SGS 国网认证等;
- 产品认证: ROHS&REACH/无卤等;
- Having good isolation, the input and output terminals are completely electrically isolated;
- Ideal spectral matching between luminescent and photosensitive devices, fast response, high transmission efficiency, and easy connection to logic circuits;
- Unidirectional transmission of optical signals effectively blocks electrical connections in circuits, but does not cut off signal transmission between them;
- Safety certification: CQC/UL/VDE/SGS State Grid certification, etc;
- Product certification: ROHS&REACH/halogen-free, etc;

应用领域

Application field

- 汽车驱动电控系统
- Automotive Drive Electronic Control System
- 光伏逆变
- Photovoltaic inverter
- 电池检测
- Battery Testing









封装形式

Package form



技术参数 Technical Specifications

Technical Specifications	Part Number	VF (V)	VL (AC)	IL (A)	Ton(ms)	Toff(ms)	Viso (Vrms)
SOP-4 »  Pin Configuration 1.Anode 2.Cathode 3.Drain1 4.Drain2	AT173	1.3-1.4	100	1.25	0.12-1	0.42-1	3750
SOP-4 »  Pin Configuration 1.Anode 2.Cathode 3.Drain1 4.Drain2	AT172	1.3-1.4	60	0.5	0.17-2	0.14-1	3750
	AT174	1.3-1.4	400	0.12	0.08-1	0.4-1	3750
	AT175	1.3-1.4	200	0.18	0.16-2	0.14-1	3750
	AT176	1.3-1.4	600	0.04	0.06-2	0.33-1	3750
	AT1722	1.3-1.4	60	2.0	1.2-5	0.5-1	3750
DIP-4/SND-4/DIP4-M »  Pin Configuration 1.Anode 2.Cathode 3.Drain1 4.Drain2	AT212	1.3-1.4	60	0.5	0.4-2	0.25-1	5000
	AT213	1.3-1.4	110	1.25	0.25-1	0.3-1	5000
	AT214	1.3-1.4	400	0.12	0.06-2	0.4-1	5000
	AT216	1.3-1.4	600	0.04	0.12-2	0.35-1	5000
DIP-8/SND-8 »  Pin Configuration 1,3. Anode 2,4. Cathode 5. Drain1 6. Drain2 7. Drain3 8. Drain4	AT222	1.3-1.4	60	0.5	0.4-2	0.25-1	5000
	AT223	1.3-1.4	110	1.25	0.25-1	0.3-1	5000
	AT224	1.3-1.4	400	0.12	0.06-2	0.4-1	5000
	AT226	1.3-1.4	600	0.04	0.12-2	0.35-1	5000
	AT227	1.3-1.4	200	0.18	0.36-2	0.12-1	5000
WSOP-16 »  Pin Configuration 1,2,6,7,8. No connection 3. Do not connect (internally connected to Pin 5) 4. Anode 5. Cathode 9,10. Drain 2 (internally connected) 11,16. Drain 1 (internally connected)	ATS258	1.3-1.5	1500	0.02	0.25-1.5	0.19-0.5	3750
DIP-6/SMD-6 »  Pin Configuration 1.Anode 2.Cathode 3.N/CO 4.Drain1 5.Source 6.Drain2	AT252	1.3-1.4	60	A: 2 B: 3 C: 4	2.4-5	0.5-1	5000
	ATV252	1.3-1.5	60	A: 3,5 B: 5,0 C: 7,0	2.5-5	0.15-5	5000
	ATV253	1.3-1.4	100	0.12	0.6-2	0.03-1	5000
	ATV254	1.3-1.4	400	0.04	1.37-2	0.23-1	5000
SMD-5 »  Pin Configuration 1. AN 2. CA 3. NC/CO 4. D1 5. D2	ATY251	1.3-1.5	1500	0.02	0.3-1.5	0.28-0.5	5000
	ATY258A	1.3-1.5	1500	0.02	0.3-1.5	0.28-0.5	5000

高速光耦

HIGH SPEED OPTOCOPLER

高速光耦是一种通过光信号实现电信号隔离与传输的光电转换器件，专为高速信号传输设计，快速响应、高精度，确保数字和模拟信号稳定传输。

High speed optocoupler is a photoelectric conversion device that isolates and transmits electrical signals through optical signals. It is designed specifically for high-speed signal transmission, with fast response and high precision, ensuring stable transmission of digital and analog signals.

产品特性

Product Features

- 体积小、驱动功率小、动作速度快、工作温度范围宽；
- 具有可单向传递信息、通频宽带、寄生反馈小、消噪能力强、抗电磁干扰性能好；
- 提供快速开关速度，进而降低停滞时间并提高移动效率和精密密度，响应速度达到ns量级
- 安规认证：CQC/UL/VDE/SGS国网认证等；
- 产品认证：ROHS&REACH/无卤等；
- Small size, low driving power, fast action speed, wide working temperature range;
- It has the ability to transmit information unidirectionally, wide bandwidth, low parasitic feedback, strong noise reduction capability, and good anti electromagnetic interference performance;
- Provide fast switching speed, thereby reducing dead time and improving movement efficiency and precision, with response speed reaching the level of ns;
- Safety certification: CQC/UL/VDE/SGS State Grid certification, etc;
- Product certification: ROHS&REACH/halogen-free, etc;

应用领域

Application field

- 汽车驱动电控系统
- 仪器仪表
- 线路接收
- Automotive Drive Electronic Control System
- Instrumentation and meters
- Line reception



封装形式

Package form









技术参数







Technical Specifications

Technical Specifications	Part Number	Mbit/s	VCC (V)	Tr(us)	Tf(us)	IFon (mA)	IFoff (mA)	VF (V)	Viso (Vrms)
DIP-6/SMD-6 » 	ATH11L1	2	15	0.1	0.1	1.6	1	1.24-1.5	5000
	ATH11L2	2	15	0.1	0.1	10	1	1.24-1.5	5000
	ATH11L3	2	15	0.1	0.1	5	1	1.24-1.5	5000
Technical Specifications	Part Number	Mbit/s	VCC (V)	Tr(us)	Tf(us)	TPLH (ns)	TPHL (ns)	CMR (kv/us)	Viso (Vrms)
DIP-8/SMD-8/SOP-8 » 	ATN7720	15	5.5	30	30	55	55	10	5000
	ATN7721	25	5.5	9	8	40	40	10	5000
	ATN7723	50	5.5	8	6	22	22	10	5000
	ATC0720	15	5.5	30	30	55	55	10	3750
	ATC0721	25	5.5	9	8	40	40	10	3750
	ATC0723	50	5.5	8	6	22	22	10	3750
SOP-5 » 	ATM720	15	5.5	30	30	55	55	10	3750
	ATM721	25	5.5	9	8	40	40	10	3750
	ATM723	50	5.5	8	6	22	22	10	3750
SOP6-P/SOP6-W » 	ATW720	15	6.0	30	30	55	55	10	5000
	ATW721	25	6.0	9	8	40	40	10	5000
	ATW723	50	6.0	8	6	22	22	10	5000
SOP-8 » 	ATC74L	15	5.5	3.5	3.5	55	55	10	3750
	AT074L	15	6.0	20	25	50	50	10	3750
	AT075L	15	6.0	6	4	80	80	10	3750
	ATC64L	10	5.5	10	10	80	80	10	5000
WDIP-8/WSMD-8/WSOP-8 » 	ATN261L	10	5.5	10	10	95	95	20	5000
	ATC261L	10	5.0	10	10	90	90	20	5000

技术参数 Technical Specifications

Technical Specifications	Part Number	Mbit/s	VCC (V)	Tr(us)	Tf(us)	TPHL (ns)	TPHL (ns)	CMR (kv/us)	Viso (Vrms)
DIP-8/SMD-8 »  Pin Configuration 1.NC 2.Anode 3.Cathode 4.NC 5.GND 6.VO 7.VB 8.VCC	AT6N135	1	30	5	50	2	1	10	5000
	AT6N136	1	30	15	50	2	1	10	5000
	ATN135	1	30	15	50	0.8	1	10	5000
	ATN136	1	30	15	50	0.8	0.8	10	5000
SOP-8/WSOP-8 »  Pin Configuration 1.NC 2.Anode 3.Cathode 4.NC 5.GND 6.VO 7.VB 8.VCC	AT0501	1	30	5	50	0.8	0.8	5	3750
	AT0511	1	30	15	50	0.8	0.8	5	3750
	ATC501	1	30	15	50	0.8	0.8	5	3750
	ATC511	1	30	15	50	0.8	0.8	5	3750
SOP6-P/SOP6-W »  Pin Configuration 1.Anode 2.NC 3.Cathode 4.GND 5.VO 6.VCC	ATW501	10	5.5	10	10	95	95	20	5000
	ATW511	10	5.0	10	10	90	90	20	5000
DIP-8/SMD-8 »  Pin Configuration 1.NC 2.Anode 3.Cathode 4.NC 5.GND 6.VO 7.VB 8.VCC	AT6N137	10	7.0	30	10	41	50	5	5000
	ATN137	10	7.0	30	10	41	50	5	5000
SOP-8 »  Pin Configuration 1.NC 2.Anode 3.Cathode 4.NC 5.GND 6.VO 7.VB 8.VCC	AT0601	10	5.5	-	-	75	75	5	3750
	AT0611	10	5.5	-	-	75	75	20	3750
	ATC601	10	5.5	-	-	75	75	5	5000
	ATC611	10	5.5	-	-	75	75	20	5000
SOP-8 »  Pin Configuration 1.Anode 1 2.Cathode 1 3.Cathode 2 4.Anode 2 5.GND 6.VO 2 7.VO 1 8.VCC	AT0630	10	5.5	-	-	75	75	5	3750
	AT0631	10	5.0	-	-	75	75	20	3750

技术参数 Technical Specifications

Technical Specifications	Part Number	Mbit/s	VCC (V)	Tr(us)	Tf(us)	TPHL (ns)	TPHL (ns)	CMR (kv/us)	Viso (Vrms)
WDIP10/WSMD10 »  Pin Configuration 1.NC 2.Anode 3.Cathode 4.NC 5.NC 6.GND 7.NC 8.VO 9.VE 10.VCC	AT2601	10	5.5	-	-	12	12	20	5000
WSOP-16 »  Pin Configuration 2,7: Anode 4,5: Cathode 1,3,6,8: NC 9: GND 16: VCC 10,15: NC 11: VO1 12: VO2 13: VO4 14: VO4	AT6N437	10	5.5	-	-	1	1	5	5000
SOP-5 »  Pin Configuration 1.Anode 2.Cathode 3.GND 4.VO 5.VCC	ATM501	1	30	-	-	150	200	5	3750
	ATM511	1	30	-	-	150	200	15	3750
SOP-8 »  Pin Configuration 1.Anode 1 2.Cathode 1 3.Cathode 2 4.Anode 2 5.GND 6.VO 2 7.VO 1 8.VCC	AT0530	1	30	-	-	1.5	1.5	10	3750
	AT0531	1	30	-	-	0.8	0.8	10	3750
	AT0534	1	30	-	-	0.8	0.8	30	3750
SOP-5 »  Pin Configuration 1.Anode 2.Cathode 3.GND 4.VO 5.VCC	ATM600	10	7.0	40	10	41	50	-	3750
	ATN601	10	7.0	40	10	41	50	5	3750
	ATM611	10	7.0	40	10	41	50	20	3750
SOP-5 »  Pin Configuration 1.Anode 2.Cathode 3.GND 4.VO 5.VCC	ATW601	10	5.5	-	-	0.1	0.1	5	3750
	ATW611	10	5.5	-	-	0.1	0.1	20	3750

栅极驱动光耦

IGBT DRIVE OPTOCOPLER

IGBT驱动光耦是一种特殊设计的光电耦合器，专为IGBT设计的高效、稳定的驱动光耦，通过光电隔离技术避免电气噪声干扰。

IGBT driven optocoupler is a specially designed optocoupler designed for IGBT with high efficiency and stability. It avoids electrical noise interference through optoelectronic isolation technology.

产品特性

Product Features

- 栅极驱动光耦用于控制电路和高压之间，提供增强的电绝缘；
- 此类光耦适合驱动功率IGBT和MOSFET，较高的输出电压能达到功率器件的栅极电压驱动要求；
- 其抑制高共模噪声的能力可防止在高频开关期间功率半导体误动作；
- 安规认证：CQC/UL/VDE/SGS国网认证等；
- 产品认证：ROHS&REACH/无卤等；
- Gate driven optocouplers are used to provide enhanced electrical insulation between control circuits and high voltages;
- This type of optocoupler is suitable for driving power IGBT and MOSFET, and the higher output voltage can meet the gate voltage driving requirements of power devices;
- Its ability to suppress high common mode noise can prevent the misoperation of power semiconductors during high-frequency switching;
- Safety certification: CQC/UL/VDE/SGS State Grid certification, etc;
- Product certification: ROHS&REACH/halogen-free, etc;

应用领域

Application field

- 伺服电机
- 工业变频器
- 电力控制
- Servo motor
- Industrial frequency converter
- Power control








封装形式

Package form



技术参数

Technical Specifications

Technical Specifications	Part Number	IO (REAK)	IFLH (mA)	VCC-VSS (V)	TPLH (ns)	TPHL (ns)	CMR (kv/us)	Viso (Vrms)
DIP-8/SMD-8/DIP8-M » 	AT3150	0.6	5	30	0.5	0.5	35	5000
	AT3120	3	5	30	0.4	0.4	35	5000
	AT0314	0.6	7	30	0.7	0.7	25	3750
	AT0341	3	4	30	0.2	0.2	35	3750
	AT0343	4	4	30	0.5	0.5	35	3750
	ATN3120	2	8	35	0.5	0.5	35	5000
	ATN3150	0.6	5	30	0.5	0.5	35	5000
DIP-8/SMD-8/DIP8-M » 	AT350	2.5	5	30	0.4	0.4	25	5000
	ATN350	2.5	5	30	0.4	0.4	25	5000
SOP-5 » 	ATM341	3	4	30	0.2	0.2	35	3750
	ATM343	4	4	30	0.2	0.2	35	3750
SOP-5 » 	AT155	0.6	7.5	30	170	200	20	3750
SOP6-W/SOP6-P » 	AT314	0.6	7	30	0.7	0.7	35	5000
	AT340	1	4	30	0.2	0.2	35	5000
	AT341	3	4	30	0.2	0.2	35	5000
	AT343	4	4	30	0.2	0.2	35	5000

智能栅极驱动光耦

INTELLIGENCE IGBT DRIVE OPTOCOPLER

智能栅极驱动光耦是一种高度集成的功率控制器件，它将TTL输入逻辑电平允许与微控制器直接接口，输出为IGBT提供局部保护，以防止过流期间产生损坏，第二个光链路为微控制器提供完全隔离的故障状态反馈信号。内置“看门狗”电路监测电源电压，以防止IGBT出现栅极驱动电压不足的现象。这种集成IGBT栅极驱动器旨在提高电机驱动器的性能和可靠性。

Intelligent gate driven optocoupler is a highly integrated power control device that allows TTL input logic level to interface directly with the microcontroller. The output I provides local protection for IGBT to prevent damage during overcurrent, and the second optical link provides completely isolated fault status feedback signal for the microcontroller. The built-in "watchdog" circuit monitors the power supply voltage to prevent IGBT from experiencing insufficient gate drive voltage. This integrated IGBT gate driver aims to improve the performance and reliability of motor drivers.

产品特性

Product Features

- 相对于栅极驱动光耦，智能IGBT栅极驱动光耦包含各种保护功能；
- 有源米勒钳和故障输出功能，以保护IGBT免受逆变器和
其他电路产生的电流；
- 安规认证：CQC/UL/VDE/SGS国网认证等；
- 产品认证：ROHS&REACH/无卤等；
- Compared to gate driven optocouplers, intelligent IGBT gate driven optocouplers include various types Protection function;
- Active Miller clamp and fault output function to protect IGBT from inverter and Current generated by other circuits;
- Safety certification: CQC/UL/VDE/SGS State Grid certification, etc;
- Product certification: ROHS&REACH/halogen-free, etc;

应用领域

Application field

- 工业逆变器及UPS电源等
Industrial inverters and UPS power supplies, etc
- IGBT和功率MOS隔离驱动(比如大功率电源板)
IGBT and power MOS isolated drive (such as high-power power boards)
- 无刷电机驱动(比如工业应用:电梯马达、水泵等)
Brushless motor drive (such as industrial applications: elevator motors, water pumps, etc.)



封装形式

Package form



技术参数 Technical Specifications

Technical Specifications	Part Number	IFON (mA)	VCC2-VEE (V)	IOH (A)	IOL (A)	TPH (ns)	TPHL (ns)	CMR (kv/us)	Viso (Vrms)
WSOP-16 >> 	AT330J	7-16	0-15	1.5	1.5	50-250	50-250	15	5000
	AT331J	7-16	-0.5-35	1.5	1.5	50-250	50-250	15	5000
	AT332J	7-16	15-30	2.5	2.5	50-250	50-250	50	5000
	AT333J	7-16	-0.5-35	2.5	2.5	50-250	50-250	50	5000
WSOP-16 >> 	AT316J	-	15-30	2.5	2.5	100-500	100-500	15-30	5000

智能功率模块化接口光耦

SMART POWER MODULE MODULAR INTERFACE OPTOCOUPLER

智能功率模块化接口光耦是专为IPM模块设计的高端光电耦合器,实现信号之间的高效电气隔离,确保IPM模块在运行时的效率、稳定和可靠性,为系统的持续稳定驱动提供有力保障。

The intelligent power module modular interface optocoupler is a high-end photoelectric coupler specifically designed for IPM modules, achieving efficient electrical isolation between signals. It ensures the high efficiency, stability, and reliability of IPM modules during operation, providing robust support for the continuous and stable driving of the system.

产品特性

Product Features

- 拥有短传播延迟、快速IGBT开关;
- 高共模瞬变抑制能力和宽工作温度范围;
- 智能功率模块化接口光耦一般是具有CMR的智能功率模块化的门级驱动接口光耦;
- 安规认证: CQC/UL/VDE/SGS国网认证等;
- 产品认证: ROHS&REACH/无卤等;
- Having short propagation delay and fast IGBT switch; High common mode transient suppression capability and wide operating temperature range;
- Intelligent power modular interface optocouplers are generally gate level drive interface optocouplers with CMR;
- Safety certification: CQC/UL/VDE/SGS State Grid certification, etc;
- Product certification: ROHS&REACH/halogen-free, etc;

应用领域

Application field

- 通用数字隔离
Universal digital isolation
- 工业变频器
Industrial frequency converter
- IPM接口隔离(比如家用电器:空调、洗衣机等)
IPM interface isolation (such as household appliances: air conditioning, washing machines, etc.)










封装形式

Package form



技术参数

Technical Specifications

Technical Specifications	Part Number	IFON (mA)	VSS (V)	VO (V)	TPH (ns)	TPHL (ns)	CMR (kv/us)	Viso (Vrms)
SOP6-P/SOP6-W >> 	AT480	2.5-5.0	25	-0.5-25	110-350	150-350	20	5000
SOP-5 >> 	ATM480	2.5-5.0	25	-0.5-25	150-350	150-350	20	3750
SOP6-P/SOP6-W >> 	AT481	3.5-5.0	25	-0.5-25	100-350	100-350	20	5000
SOP-5 >> 	ATM481	3.5-5.0	25	-0.5-25	100-350	100-350	20	3750
SOP-5 >> 	ATM456	0.96-5.0	30	-0.5-25	300-400	220-650	15-30	3750
DIP-8/SMD-8 >> 	AT4504	8-16	-0.5-30	-0.5-20	300-800	200-700	15-30	5000
	ATC4504	8-16	-0.5-30	-0.5-20	300-800	200-700	15-30	5000
	ATN4504	8-16	-0.5-30	-0.5-20	300-800	200-700	15-30	5000
DIP-8/SMD-8 >> 	AT4506	8-16	-0.5-30	-0.5-20	300-800	200-700	15-30	5000
	ATC4506	8-16	-0.5-30	-0.5-20	300-800	200-700	15-30	5000
	ATN4506	8-16	-0.5-30	-0.5-20	300-800	200-700	15-30	5000

光隔离运算放大器

OPTICAL ISOLATION OPERATIONAL AMPLIFIER

光隔离运算放大器的输入与输出级间可以承受5000V以上的绝缘电压,适用于各种逆变器产品及带马达的产品

The input and output stages of the optically isolated operational amplifier can withstand insulation voltages of over 5000V, making it suitable for various inverter products and products with motors

产品特性

Product Features

- 输入与输出级间可以承受5000V以上的绝缘电压;
- 抗干扰能力强、工作稳定、无触点、使用寿命长、传输速率高;
- 信号单向传输,输入端与输出端完全实现电气隔离,输出信号对输入端无影响;
- 安规认证: CQC/UL/VDE/SGS 国网认证等;
- 产品认证: ROHS&REACH/无卤等;
- The insulation voltage between the input and output stages can withstand over 5000V;
- Strong anti-interference ability, stable operation, contactless, long service life, and high transmission rate;
- Unidirectional transmission of signals, complete electrical isolation between input and output terminals, and no impact of output signals on input terminals;
- Safety certification: CQC/UL/VDE/SGS State Grid certification, etc;
- Product certification: ROHS&REACH/halogen-free, etc;

应用领域

Application field

- 信号采集(马达相位、线路电压/电流等)
Signal acquisition (motor phase, line voltage/current, etc.)
- 带马达的产品(检测马达相位和线路接收)
Products with motors (detecting motor phase and line reception)
- 逆变器产品(线路过流检测等)
Inverter products (line overcurrent detection, etc.)



封装形式

Package form



技术参数 Technical Specifications

Technical Specifications	Part Number	Gain Error (MAX. %)	Nonlinear (Typ. %)	Band width (KHZ)	VDD (V)	CMR (kv/us)	Viso (Vrms)
DIP-8/WSOP-8 >>	AT7840	±5	0.0037	100	5.5	10	5000
	ATC790	±3	0.05	200	5.5	10	5000
	ATC79A	±1	0.05	200	5.5	10	5000
	ATC79B	±0.5	0.05	200	5.5	10	5000
	ATH790	±3	0.05	200	5.5	15	5000
WSOP-8 >>	ATC87AT	±1	0.05	100	5.5	10	5000
	ATC87BT	±0.5	0.05	100	5.5	10	5000

栅极驱动光耦品牌型号对应参照表

Reference table for brands and models of gate driven optocouplers

奥特 AOTE	安华高 AVAGO	仙童 FAIRCHILD	东芝 TOSHIBA	夏普 SHARP	瑞萨 RENESA	威世 VISHAY	光宝 LITEON	亿光 EVERLIGHT	冠西 COSMO	奥伦德 ORIENT	德州仪器 Texas Instruments
AT155	—	—	TLP155A TLP155E	—	—	—	LTV-155E	—	—	OR-155E	—
AT3120	ACPL-312T ACPL-3350 ACPL-3313 HCPL-0302 HCPL-3020 HCPL-3120 HCPL-3140 HCPL-3180 HCPL-3312 HCPL-T250 HCPL-T251	FOD3120 FOD3125SD MOC3120	TLP352 TLP350 TLP350H TLP250 TLP250H TLP2451A TLP351A	PC925LONS20F PC925LENIP0F PC942J	PS9505 PS9506 PS9552	VO3120	LTV- T350 LTV- 3120	EL3120	KTLP250 KTLP350	OR-3120	—
AT3150	QCPL-341H HCPL-3150 HCPL- J314	FOD3150	TLP250	PC923 PC924	PS9553	VO3150	LTV- 3150	—	—	OR-3150	—
AT314	ACPL- W314 ACPL- P314	FOD8314	TLP701A TLP705A TLP701 TLP5701 TLP5751	—	—	—	LTV- 314	—	—	OR- 314	—
AT340	ACPL- P302 ACPL- W302 ACPL- P340 ACPL- W340	—	—	—	—	—	LTV- 340	—	—	OR- 340	—
AT341	ACPL- P341 ACPL- W341 ACPL- P346 ACPL- W349	FOD8342	TLP5702 TLP5702H TLP5752 TLP5772 TLP700AF	—	—	VOL3120	LTV- 341	—	—	OR- 341	UCC23511 UCC23513
AT343	ACPL- P343 ACPL- W343	—	TLP5754	—	—	—	—	—	—	—	—
ATM341	—	—	TLP152	—	—	—	—	—	—	—	—
ATN3120	HCNW-3120	—	—	—	—	—	—	—	—	—	—
AT316J	HCPL- 316J ACPL- 316J	FOD8316	—	—	—	—	LTV-316J	—	—	—	—
AT330J AT331J AT332J	ACPL- 330J QCPL- 329J ACPL- 331J ACPL- 332J	—	TLP5214A	—	—	—	—	LTV- 332J	—	—	—
AT333J	ACPL- 333J	—	—	—	—	—	—	—	—	—	—

智能功率模块接口光耦品牌型号对应参照表

Reference Table for Brand and Model of Intelligent Power Module Interface Optocoupler

奥特 AOTE	安华高 AVAGO	仙童 FAIRCHILD	东芝 TOSHIBA	夏普 SHARP	瑞萨 RENESA	威世 VISHAY	光宝 LITEON	亿光 EVERLIGHT	冠西 COSMO	奥伦德 ORIENT
AT4504	HCPL- 4504	—	—	—	—	—	—	—	—	—
AT4506	HCPL- 4506	—	—	—	—	—	—	—	—	—
AT4800	—	—	—	—	—	—	—	—	—	—
AT480	ACPL- P480	—	TLP2745 TLP715	—	—	—	LTV-480P LTV- 480W	—	—	—
AT481	ACPL- M483	—	TLP2704	—	—	—	—	—	—	—
ATM456	—	—	—	—	—	—	—	—	—	—
ATM480	—	—	TLP2345 TLP2355 TLP105	—	—	—	LTV- 480	—	—	—
ATM481	ACPL - P456	—	TLP108 TLX9304	—	—	—	LTV- 481	—	—	—

隔离运算放大器品牌型号对应参照表

Reference table for brands and models of isolated operational amplifiers

奥特 AOTE	安华高 AVAGO	仙童 FAIRCHILD	东芝 TOSHIBA	夏普 SHARP	瑞萨 RENESA	威世 VISHAY	光宝 LITEON	亿光 EVERLIGHT	冠西 COSMO	奥伦德 ORIENT
AT7840	HCPL-7840									
ATC790	ACPL- C790									
ATC79A	ACPL-C79A									
ATC79B ATC87AT	ACPL-C79B ACPL-C87AT									
ATC87BT	ACPL-C87BT									